

Copying Synchronizers



Dark Feature - Synchronizers are hidden by default

We recommend using [Automation](#) instead of Synchronizers. Automation is safer, provides additional functionality and flexibility, and uses fewer system resources.

To enable synchronizers, see [Advanced Configuration and Dark Features](#).

When [copying a structure](#) that has synchronizers, you can use the **Copy Synchronizers** option to make Structure create a copy of every synchronizer installed in the original structure.



If you don't see the **Copy Synchronizers** option, you may not have permission to create synchronizers.

Copying Parameters

Synchronizers

2

Sub-Tasks (Sub-task, Technical task)

Links (Blocks)

Copy Synchronizers?

☐ No

☒ Yes

Synchronizer ownership:

☒ Leave as is

☐ Make me (admin) the new owner

You can decide to leave the original ownership of a synchronizer ("**Run As**" parameter) or make yourself a new owner for each of the copied synchronizers.



Only Jira administrators can change the synchronizer ownership.



Making yourself the new owner means that all synchronizers in the copied structure will run under your account.

Required Permissions

To be able to copy synchronizers, you need permissions to [create and configure synchronizers](#).

Enabling Copied Synchronizers

After the structure is copied, all copied synchronizers are initially disabled. To enable them:

1. Review their configuration to ensure they still meet your needs
2. Adjust as necessary
3. Run **Resync & Enable** - this does an initial sync and enables the synchronizers to run in the background